

**ROADWIN***Stay on your way*

LIGHTS



"O.E.M and other manufacturers names, part numbers and images are used for reference only"

28.1 SIDE MARKERS



A15012

Side	Voltage, V	Description
	12 - 24	LED, 110x45x24



A15002

Side	Voltage, V	Description
Right	12 - 24	Red/white LED, long, hooked

A15003

Side	Voltage, V	Description
Left	12 - 24	Red/white LED, long, hooked



A15004

Side	Voltage, V	Description
Right	12 - 24	Red/white LED, long, diagonal

A15005

Side	Voltage, V	Description
Left	12 - 24	Red/white LED, long, diagonal



A15016

Side	Voltage, V	Description
	24	102x54x14, W5W



A15021

Side	Voltage, V	Description
	24	102x54x14, W5W, LED



A15017

Side	Voltage, V	Description
	12 - 24	Yellow

**A15021**

Side	Voltage, V	Description
	24	102x54x14, W5W, LED

28



A15121



Power, W	Voltage, V	Description
27	DC9-48	Current Draw: 1.7A=12V, 0.9A=24V Lumens: 1800LM Color temperature: 6000K IP67

A15122



Power, W	Voltage, V	Description
42	DC9-32	Current Draw: 3A=12V, 1.5A=24V Lumens: 3000LM Color temperature: 6000K IP67

A15123



Power, W	Voltage, V	Description
27	DC10-30V	Lumens: 1700LM Color temperature: 6000-6500K IP68 WITH EMARK

A15113



Power, W	Voltage, V	Description
27	DC10-30	Lumens: 1700LM Color temperature: 6000-6500K IP68 WITH EMARK

A15114



Power, W	Voltage, V	Description
48	DC10-30	Lumens: 3500LM Color temperature: 6000-6500K IP68 WITH EMARK

A15131



Power, W	Voltage, V	Description
18	DC9-32	Current Draw: 1.4A=12V, 0.75A=24V Lumens: 1170LM Color temperature: 6500K IP67



28



Roadwin	Power, W	Voltage	Length, mm	Description
A15202	36	DC10-30V	152,4	Operating temperature: -40C ~ 60C, Lumens: 2880LM Color temperature: 6000K IP68
A15203	54	DC10-30V	228,6	Operating temperature: -40C ~ 60C, Lumens: 4320LM Color temperature: 6000K IP68
A15204	72	DC10-30V	304,8	Operating temperature: -40C ~ 60C, Lumens: 5760LM Color temperature: 6000K IP68
A15205	90	DC10-30V	355,6	Operating temperature: -40C ~ 60C, Lumens: 7200LM Color temperature: 6000K IP68
A15206	108	DC10-30V	431,8	Operating temperature: -40C ~ 60C, Lumens: 8640LM Color temperature: 6000K IP68
A15208	144	DC10-30V	558,8	Operating temperature: -40C ~ 60C, Lumens: 11520LM Color temperature: 6000K IP68
A15209	180	DC10-30V	711,2	Operating temperature: -40C ~ 60C, Lumens: 14400LM Color temperature: 6000K IP68
A15210	198	DC10-30V	787,4	Operating temperature: -40C ~ 60C, Lumens: 13860LM Color temperature: 6000K IP68
A15213	288	DC10-30V	1117,6	Operating temperature: -40C ~ 60C, Lumens: 24000LM Color temperature: 6000K IP68



Roadwin	Power, W	Voltage	Length, mm	Description
A15251	144	DC10-30V	1248	Operating temperature: -40C ~ 60C, Lumens: 10080LM Color temperature: 6000K IP68, COMBO



Roadwin	Power, W	Voltage	Length, mm	Description
A15221	36	DC10-30V	236	Operating temperature: -40C ~ 60C, Lumens: 2520LM Color temperature: 6000K IP68
A15222	72	DC10-30V	389	Operating temperature: -40C ~ 60C, Lumens: 5040LM Color temperature: 6000K IP68



A15401



A15402

Roadwin	Power, W	Description
A15401	280	LED bar cable
A15402	280	LED bar cable with remote control



A15403

Light bar mount bracket

LED LAMPS WITH EMARK



28



Roadwin	Power, W	Voltage	Length, mm	Description
A15322	120	DC10-32V	558,8	Lumens: 7200LM Color temperature: 5000K or 6000K IP67
A15324	180	DC10-32V	812,8	Lumens: 10800LM Color temperature: 5000K or 6000K IP67
A15325	240	DC10-32V	1066,8	Lumens: 14400LM Color temperature: 5000K or 6000K IP67

28



Roadwin	Power, W	Voltage	Length, mm	Description
A15290	36	DC10-30V	203,2	Lumens: 3240/2880LM Color temperature: 6000K IP68
A15291	72	DC10-30V	355,6	Lumens: 6480/5760LM Color temperature: 6000K IP68
A15292	120	DC10-30V	558,8	Lumens: 10800/9600LM Color temperature: 6000K IP68
A15293	144	DC10-30V	660,4	Lumens: 12960/11520LM Color temperature: 6000K IP68
A15294	180	DC10-30V	812,8	Lumens: 16200/14400LM Color temperature: 6000K IP68
A15295	240	DC10-30V	1066,8	Lumens: 21600/19200LM Color temperature: 6000K IP68
A15296	288	DC10-30V	1270	Lumens: 25920/23040LM Color temperature: 6000K IP68
A15297	300	DC10-30V	1320,8	Lumens: 27000/24000LM Color temperature: 6000K IP68



28



Roadwin	Power, W	Voltage	Length, mm	Description
A15260	60	DC10-30V	203,2	Lumens: 2448/6000LM Color temperature: 6000K IP68
A15261	80	DC10-30V	254	Lumens: 3090/8000LM Color temperature: 6000K IP68
A15262	100	DC10-30V	304,8	Lumens: 3500/10000LM Color temperature: 6000K IP68
A15263	120	DC10-30V	355,6	Lumens: 5084/12000LM Color temperature: 6000K IP68
A15264	160	DC10-30V	457,2	Lumens: 5600/16000LM Color temperature: 6000K IP68
A15265	180	DC10-30V	508	Lumens: 6300/18000LM Color temperature: 6000K IP68
A15266	200	DC10-30V	584,2	Lumens: 7000/20000LM Color temperature: 6000K IP68
A15267	240	DC10-30V	685,8	Lumens: 8400/24000LM Color temperature: 6000K IP68
A15268	300	DC10-30V	838,2	Lumens: 10500/30000LM Color temperature: 6000K IP68
A15269	340	DC10-30V	939,8	Lumens: 11900/34000LM Color temperature: 6000K IP68
A15270	400	DC10-30V	1092,2	Lumens: 14000/40000LM Color temperature: 6000K IP68
A15271	440	DC10-30V	1193,8	Lumens: 15400/44000LM Color temperature: 6000K IP68
A15272	500	DC10-30V	1346,2	Lumens: 17500/50000LM Color temperature: 6000K IP68



Roadwin	Power, W	Voltage	Length, mm	Description
A15330	30	DC10-30V	178	Dual row LED light bar with indication
A15331	60	DC10-30V	304,8	Dual row LED light bar with indication
A15332	120	DC10-30V	558,8	Dual row LED light bar with indication
A15333	180	DC10-30V	813	Dual row LED light bar with indication
A15334	240	DC10-30V	1066,8	Dual row LED light bar with indication
A15335	300	DC10-30V	1321	Dual row LED light bar with indication



28



Roadwin	Power, W	Voltage	Length, mm	Description
A15280	32	DC10-30V	177,8	Lumens: 2448/6000LM Color temperature: 6000K IP68
A15281	64	DC10-30V	304,8	Lumens: 3090/8000LM Color temperature: 6000K IP68
A15282	96	DC10-30V	431,8	Lumens: 3500/10000LM Color temperature: 6000K IP68
A15283	128	DC10-30V	558,8	Lumens: 5084/12000LM Color temperature: 6000K IP68
A15284	192	DC10-30V	812,8	Lumens: 5600/16000LM Color temperature: 6000K IP68
A15285	256	DC10-30V	1066,8	Lumens: 6300/18000LM Color temperature: 6000K IP68
A15286	320	DC10-30V	1320,8	Lumens: 7000/20000LM Color temperature: 6000K IP68